


Barriers to WDM Deployment on Military Platforms

**John Gallo
BAE SYSTEMS
Aerospace Electronics
Lansdale, PA 19446**

**DARPA/MTO
WDM for Military Platforms Workshop
18 April 2000**


Militarized (Flight-Qualified) 18 GHz Single-Mode Transmitters

BAE SYSTEMS




Mature, Military Hardware for Point-to-Point Applications

RF Flatness over Frequency @ 90C




Mean Optical Output Power vs. Temperature



REVIEW OF THIS MATERIAL DOES NOT IMPLY
DEPARTMENT OF DEFENSE INDORSEMENT OF
FACTUAL ACCURACY OR OPINION

Generic WDM for Non-Blocking, Full Broadcast Antenna Selection




WDM Fiber Network Replacing Conventional RF Cabling, Optical Power Divider (PD) and Optical Tunable Filters (OTF) Replacing Conventional RF Switch; All Antenna Signals Available at Each Receiver

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED




REVIEW OF THIS MATERIAL DOES NOT IMPLY
DEPARTMENT OF DEFENSE INDORSEMENT OF
FACTUAL ACCURACY OR OPINION

Current Analog 18 GHz Link WDM System

(80 Antennas to 16 Receivers using 4 Wavelengths)





Dual Channel (10.1 and 10.5 GHz) Switching (Optical Tunable Filter)



Switching Speed ~80 ns
RF Crosstalk <-76 dBc
RF Bandwidth 18 GHz
Insertion Loss ~8 dBc

Low Noise Optically Amplified Microwave Links



BAE SYSTEMS has developed proprietary technology to reduce the noise figure (RIN ~ -157 dB/Hz) of fiber optic microwave links with high optical processing losses due to WDM, switching, and other distribution components.

Desparately Needed Developments to Enable Replacement of RF Switches

- **Low Insertion Loss, High-Speed Switches**
 - 10 ms SONET Switching is Too Slow for Military Applications
 - $<10 \mu\text{s}$ is Typical Requirement ($<100 \text{ ns}$ for High POI Appl.)
 - Narrow Bandwidth (FP), High-Speed Switches Don't Help!!
- **Low-RIN EDFAs**
 - WDM Requires Muxing and Demuxing Multiple Channels
 - EDFAs **ALWAYS** Degrade Analog Link Performance
 - EDFA RIN Must be Reduced Below -155 dB/Hz
- **High Crosstalk Suppression Between WDM Channels (Optical Switches for Tunable λ Filtering)**
 - Easy for Narrowband RF Signals ($<1 \text{ GHz}$)
 - Difficult for 18 GHz and Higher Sidebands
 - Fiber Bragg Gratings are the Only Demonstrated Technology to Achieve $> 35 \text{ dBo}$ Crosstalk Suppression for 18 GHz Sidebands
- **High-Power WDM DFB Arrays**
 - $>40 \text{ mW/Channel}$ @ RIN $<-160 \text{ dB/Hz}$, $< 1 \text{ MHz}$ Linewidth